

The TACO logo features the word "TACO" in a bold, white, sans-serif font. A small orange square is positioned at the top left of the letter "T".

TACO

The text "LUXURY SPC FLOORING" is written in a tall, white, sans-serif font, oriented vertically. To the left of this text, the number "5" is displayed in a large, bold, white font, followed by "mm" in a smaller font, and "SPC CLICK" in a bold, white font.

LUXURY SPC FLOORING

5 mm SPC
CLICK

MAKE THAT CHANGE

STONE SERIES

Wear Layer 0.3mm | Thickness 5.0mm | Size 300mm x 600mm | 12 pieces / box (2.16sqm)



TV 5513 SPC Rustico - Bronze



TV 5514 SPC Rustico - Taupe



TV 5515 SPC Rustico - Graphite



TV 5516 SPC Concrete



Built-in 1mm IXPE Underlay

Easy application with
Click System technology



WOOD SERIES

Wear Layer 0.3mm | Thickness 5.0mm | Size 172mm x 1210mm | 11 pieces / box (2.29sqm)



TV 5501 SPC Tuscany Oak



TV 5507 SPC Finnish Oak



TV 5502 SPC Ottawa Oak



TV 5508 SPC Madeira Walnut



WOOD SERIES

Wear Layer **0.3mm** | Thickness **5.0mm** | Size **172mm x 1210mm** | 11 pieces / box **(2.29sqm)**



TV 5503 SPC Valencia Oak



TV 5510 SPC Canyon Oak



TV 5509 SPC Wild Cherry



TV 5506 SPC Glenmore Oak



TV 5504 SPC Golden Acacia



TV 5511 SPC Ontario Hickory



TV 5505 SPC Carson Oak



TV 5512 SPC Somerset Applewood



TACO Luxury SPC Flooring | SPC 5mm

CLICK

TECHNICAL DATA

CHARACTERISTICS	TEST METHOD	PASS
Overall thickness	ASTM F386-11	✓
Thickness of wear layer	ASTM F410-08 (2013)	✓
Residual indentation	ASTM F1914-07 (2011)	✓
Dimension stability	ASTM F2199-09 (2014)	✓
Resistance to chemical	ASTM F925-13	✓
Resistance to heat	ASTM F1514-03 (2013)	✓
Resistance to light	ASTM F1515-15	✓
Castor chair	NALFA LF 01-2011 : No Obvious Damage	✓
Fungi resistance	ASTM G21-15 : Rating 0, no growth	✓
Formaldehyde content	ASTM D6007-14 : Not Detected	✓
Impact resistance	DIN 51130:2014	✓
Reaction to fire	EN 13501-1	✓

PRODUCED UNDER HIGH QUALITY SUPERVISION WITH ISO 9001 ISO 14001 OHSAS 18001 CE STDS.



Click
System



0.3mm
Wear Layer



100%
Waterproof



Easy to Clean
& Maintain



Termite
Proof



Simple & Quick
to Install