



TACO

LUXURY VINYL FLOORING

3
mm
LVF

MAKE THAT CHANGE

PATTERN SERIES

Wear Layer 0.2mm | Thickness 3.0mm | Size 457.2mm x 457.2mm | 16 pieces / box (3.34sqm)



TV 3027
Mozaic - Natural



TV 3028
Mozaic - Grey



STONE SERIES

Wear Layer 0.2mm | Thickness 3.0mm | Size 304.8mm x 609.6mm | 18 pieces / box (3.34sqm)



TV 3024
Grey Slate



TV 3026
Stone



TV 3025
Dark Grey Slate



WOOD SERIES

Wear Layer 0.2mm | Thickness 3.0mm | Size 152.4mm x 914.4mm | 24 pieces / box (3.34sqm)



TV 3010 Warm Cherry



TV 3006 Real Cherry



TV 3014 Natural Beech



TV 3008 Sand Malmo



TV 3009 Rich Walnut



TV 3013 White Oak



TV 3003 Washed Oak



TV 3016 Grey Oak



TV 3005 Vintage Oak



TV 3001 Rustic Oak



WOOD SERIES

Wear Layer 0.2mm | Thickness 3.0mm | Size 152.4mm x 914.4mm | 24 pieces / box (3.34sqm)



TV 3019 Victorian Barn



TV 3015 Vicenza Elm



TV 3004 Parma Oak



TV 3017 Original Cherry



TV 3007 Merbau Wood



TV 3020 Bailey Acacia



TV 3021 Scottish Applewood



FLOORING PATTERNS & LAYOUTS

BRICK



HERRINGBONE



1/3 STEP



DOUBLE HERRINGBONE



STAGGERED



DIAGONAL HERRINGBONE



TACO Luxury Vinyl Flooring | LVF 3mm

TECHNICAL DATA

CHARACTERISTICS	TEST METHOD	PASS
Resistance to chemicals	EN423:93 Class 0	✓
Bearing castor	EN425:94	✓
Dimension squareness and straightness	EN427:94	✓
Thickness overall	EN429:93	✓
Thickness wear layer	EN429:93	✓
Residual indentation after static load	EN433:94	✓
Dimensional stability and curling after exposure to heat	EN434:94	✓
Shrinkage rate	≤ 0.25%	✓
Curling	≤ 2mm	✓
Flexibility	EN435:94(A)	✓
	Bend around 20mm mandrel shows no sign of cracking	✓
Abrasion resistance	EN660-1/-2	✓
Color fastness to light	EN 20 ISO 105-B02 6 or above	✓
Toxic element test	EN 71-3	✓
Specific gravity	ASTM D792:91	✓
Coefficients of friction	ASTM D1894:01	✓
Sound reduction	DIN52210:4db	✓
Flammability	EN 71-2	✓
Smoke density	DIN4102/ASTM D2843-99:Class B1	✓
Electrical resistance	EN1081 Method C	✓
Fungus test	ASTM G21:96 Grade 1	✓
IMO resolution	MSC61(67) Part 2	✓
	MSC61(67) Part 5	✓

PRODUCED UNDER HIGH QUALITY SUPERVISION WITH ISO 9001 ISO 14001 OHSAS 18001 CE STDS.



100%
Waterproof



Easy to Clean
& Maintain



Termite
Proof



Simple & Quick
to Install